



FEATURES

PARAMETERS

Power Supply	Internal voltage 3.3V & 5V
Operation Modes	Active (turn on LINEA-PRO 5) / Active with Scanning / Standby (after 5 sec without operation)
MCU	Hitachi - HD64F3687
Memory	512k I2C EEPROM memory - for LINEA-PRO 4 settings
Communications	RS232 Interface - communication between LINEA-PRO 4 & iPod touch / iPhone USB Interface - USB synchronization between iPhone / iPod touch & PC
RS232 Interface	Speed: 57600bps iPod RS232 Protocol
RFID READER	MIFARE CLASSIC; MIFARE MINI; MIFARE ULTRALIGHT; MIFARE PLUS ISO 14443; ISO 15693 DESFire CArd
Buttons	Volume Up, Volume Down, Status Battery, Scan
Magnetic Stripe Reader	3-track bidirectional reading capabilities Type: ISO 7816-1/2/3 compatible & RAW mode
Barcode Scanner	Laser Scan Engine 1D Barcode Auto-focus Imager Scan Engine 2D Barcode
Barcode Type	UCC/EAN 128, EAN 13, EAN 8, UPC A, UPC E, UPC E1, Code 11, Code 39, Code 93, Code 128, GS1, Matrix 2 to 5, Code 11, 2 of 5 interleaved, Codebar, MSI/Plessey, UK/Plessey, IATA, ISBN, ISMN, ISSN, S-code, Telepen, RSS 14, RSS Limited, RSS-Expanded, PDF417, microPDF417, Data Matrix, QR code, Aztec code, Maxi code, Micro QR code
LEDs	4 green LEDs for status of battery charging and status of the device
Battery	Rechargeable Li-ion Battery 3.7V/1300mAh 1D: Over 14,000 scan and swipes per full charge 2D: Over 8,000 scan and swipes per full charge
Audio Indicator	Electromagnetic Buzzer
Weight	119 grams without iPod touch / iPhone
Dimensions	142mm x 69mm x (22 to 27)mm — depends on scanner 1D/2D & device
Operating Environment	- Operating temperature: 0° C to +40° C - Operating humidity: 35 to 85% RH - Storage temperature: -5° C to +40° C - Storage humidity: 10 to 90% RH
Cables	Standard USB A to mini B cable

Cidroid
Division of Nexus s.r.l.
Via Palmanova 24
20132 Milano
Italy
+39 (0)2 2666490

info@cidroid.com
www.cidroid.com

Preferred partner for Italy, Spain & Portugal

